

**IN THE CLAIMS:**

Please amend claim 1 as follows.

1. (Currently Amended) A link protocol redundancy method comprising the steps of:

providing a router having an active processor;

coupling a standby processor to said active processor;

forwarding network link protocol information from said active processor to said standby processor for synchronizing link configuration and link protocol states of said active processor at said standby processor upon coupling of said standby processor to said ~~standby~~ active processor; and

switching said router to said standby processor when a failure is detected at said active processor;

wherein all states of said link protocol immediately function as if the failure had not occurred.

2. (Original) The method of claim 1 wherein said link protocol is an Open Shortest Path First (OSPF) protocol.

3. (Original) The method of claim 2 wherein said link protocol information is link-state database information, OSPF configuration information, OSPF adjacencies information, OSPF interface information and OSPF global protocol information.

4. (Original) The method of claim 2 further comprising the step of processing identical OSPF packets after synchronizing said link configuration and link protocol states between said active processor and said standby processor

5. (Original) The method of claim 3 wherein said step of forwarding link protocol information is performed by the steps of:

creating a hidden OSPF interface for each area of said active processor;

creating a hidden OSPF interface for each area of said standby processor; and

forwarding said link-state database information from said hidden OSPF interface of said active processor to said hidden OSPF interface of said standby processor until said link state database of said standby processor is synchronized with said link state database of said active processor.

6. (Original) The method of claim 5 further comprising the step of forwarding said OSPF configuration information, OSPF adjacencies information, OSPF interface information and OSPF global protocol information using said hidden OSPF interface of said active processor and said hidden OSPF interface of said standby processor.

7. (Original) The method of claim 5 wherein said link protocol information is in the form of Inter Process Control (IPC) messages.

8. (Original) The method of claim 7 wherein said OSPF configuration

information is determined from Command Line Interface (CLI) commands stored in a datastore.

9. (Original) The method of claim 1 further comprising the steps of:  
updating network link protocol information at said active processor; and  
forwarding said updated network link protocol information to said standby processor.

10. (Original) The method of claim 4 wherein said forwarding step is a process based on a Database Exchange Process of the OSPF protocol.

11. (Original) An OSPF protocol redundancy method comprising the steps of:  
providing a router having an active processor;  
coupling a standby processor to said active processor;  
forwarding network OSPF protocol information from said active processor to said standby processor for synchronizing OSPF configuration and OSPF protocol states of said active processor at said standby processor; and  
switching said router to said standby processor when a failure is detected at said active processor;  
wherein all states of said OSPF protocol immediately function as if the failure had not occurred.

12. (Original) A link protocol redundancy method comprising the steps of:

- providing a router having an active processor;
- coupling a standby processor to said active processor;
- forwarding network link protocol information from said active processor to said standby processor for synchronizing link configuration and link protocol states of said active processor at said standby processor said link protocol information is link-state database information, OSPF configuration information, OSPF adjacencies information, OSPF interface information and OSPF global protocol information.; and
- switching said router to said standby processor when a failure is detected at said active processor;

wherein all states of said link protocol immediately function as if the failure had not occurred.

13. (Original) A method for implementing OSPF redundancy comprising the steps of:

- providing a router having an active processor means and a standby processor means;

- building a hidden OSPF interface on said active processor means and a hidden OSPF interface on said standby processor means;

- connecting said hidden OSPF interface of said active processor means to said hidden OSPF interface of said standby processor means over a communications link;

- synchronizing an OSPF routing database using an OSPF protocol over said hidden

OSPF interface, such that said OSPF routing database is synchronized when said hidden OSPF interface of said active processor means and said hidden OSPF interface of said standby processor means reach a full adjacency state;

transferring OSPF protocol information from said hidden OSPF interface of said active processor means to said hidden OSPF interface of said standby processor means over said communications link to mirror states of said active processor means and said standby processor means;

removing said hidden interface of said active processor means and said hidden interface of said standby processor means; and

assuming control by said standby processor means when a failure is detected in said active processor means.

14. (Original) The method of claim 13 wherein said OSPF protocol information is OSPF configuration information, OSPF adjacencies information, OSPF interface information and OSPF global protocol information.

15. (Original) The method of claim 14 wherein said OSPF configuration information is determined from Commercial Line Interface (CLI) commands stored in a datastore.

16. (Original) The method of claim 13 further comprising the steps of:  
updating network link protocol information at said active processor means; and

forwarding said updated network link protocol information to said standby processor means.

17. (Original) The method of claim 13 wherein said synchronizing step is a process based on a Database Exchange Process of the OSPF protocol.

18. (Original) The method of claim 13 further comprising the step of processing identical OSPF packets after synchronizing said link configuration and link protocol states between said active processor and said standby processor

19. (Original) A system for providing link protocol redundancy in a router comprising:

an active processor;

a standby processor;

means for forwarding network link protocol information from said active processor to said standby processor for synchronizing link configuration and link protocol states of said active processor at said standby processor; and

means for switching said router to said standby processor when a failure is detected at said active processor;

wherein all states of said link protocol immediately function as if the failure had not occurred.

20. (Original) The system of claim 19 wherein said link protocol is an Open Shortest Path First (OSPF) protocol.

21. (Original) The system of claim 19 wherein said link protocol information is link-state database information, OSPF configuration information, OSPF adjacencies information, OSPF interface information and OSPF global protocol information.

22. (Original) The system of claim 21 wherein said means for forwarding link protocol information comprises:

means for creating a hidden OSPF interface on for each area of said active processor;

means for creating a hidden OSPF interface for each area of said standby processor; and

means for forwarding said link-state database information from said hidden OSPF interface of said active processor to said hidden OSPF interface of said standby processor until said link state database of said standby processor is synchronized with said link state database of said active processor.

23. (Original) The system of claim 22 wherein said means for forwarding link protocol information comprises forwarding said OSPF configuration information, said OSPF adjacencies information, said OSPF interface information and said OSPF global protocol information using said hidden OSPF interface of said active processor and said

hidden OSPF interface of said standby processor.

24. (Original) The system of claim 23 wherein said OSPF configuration information is determined from Command Line Interface (CLI) commands stored in a datastore.



25. (Original) The system of claim 19 further comprising:  
means for updating network link protocol information at said active processor; and  
means for forwarding said updated network link protocol information to said  
standby processor.

26. (Original) The system of claim 19 wherein said means for forwarding  
network link protocol information comprises:

a redundant card manager for maintaining a synchronization state machine of said  
link protocol states for tasks of said protocol, said network link protocol information  
being forwarded through said redundant card manager.

27. (Original) The system of claim 19 further comprising a task manager for  
determining said link protocol states of said tasks and forwarding said link protocol states  
to said redundant card manager.

28. (Original) The system of claim 19 wherein said means for switching said  
router to said standby processor comprises a software redundancy manager which  
interacts with said redundant card manager to indicate switch over from said active  
processor to said standby processor.

29. (Original) The system of claim 19 wherein said state of said tasks enters an

OSPF\_FAULT\_INIT state which is an initial state before coupling of standby processor to said active processor.

30. (Original) The system of claim 19 wherein said state of said tasks enters an OSPF\_FAULT\_VERIFY state which is entered during synchronization of said link configuration of said active processor and said standby processor.

31. (Original) The system of claim 19 wherein said state of said tasks enters an OSPF\_FAULT\_SYNC state during forwarding of said link protocol information from said active processor to said standby processor, said link protocol information comprising link-state database information, OSPF configuration information, OSPF adjacencies information, OSPF interface information and OSPF global protocol information.

32. (Original) The system of claim 19 wherein said state of said tasks enters an OSPF\_FAULT\_FULL state after said forwarding network link protocol information, said OSPF\_FAULTFULL state is a hot standby state wherein said standby state can immediately take over all operations of said standby processor.

33. (Original) The system of claim 19 wherein said active processor is an active OSPF control card.

34. (Original) The system of claim 19 wherein said standby processor is a

standby OSPF control card.

35. (Original) The system of claim 19 wherein said means for forwarding is a process based on a Database Exchange Process of the OSPF protocol.

36. (Original) The system of claim 19 further comprising:  
means for processing identical OSPF packets after synchronizing said link configuration and link protocol states between said active processor and said standby processor.

37. (Original) A system for providing open shortest path first (OSPF) protocol redundancy in a router comprising:

an active processor;

a standby processor;

means for forwarding network open shortest path first (OSPF) protocol information from said active processor to said standby processor for synchronizing link configuration and open shortest path first (OSPF) protocol states of said active processor at said standby processor; and

means for switching said router to said standby processor when a failure is detected at said active processor;

wherein all states of said open shortest path first (OSPF) protocol immediately function as if the failure had not occurred.

38. (Original) A system for providing open shortest path first (OSPF) protocol redundancy in a router comprising:

- an active processor;
- a standby processor;
- means for forwarding network open shortest path first (OSPF) protocol information from said active processor to said standby processor for synchronizing link configuration and open shortest path first (OSPF) protocol states of said active processor at said standby processor link-state database information, OSPF configuration information, OSPF adjacencies information, OSPF interface information and OSPF global protocol information; and
- means for switching said router to said standby processor when a failure is detected at said active processor;

wherein all states of said open shortest path first (OSPF) protocol immediately function as if the failure had not occurred.

39. (Original) A system for implementing OSPF redundancy in a router comprising:

- an active processor means;
- a standby processor means;
- means for building a hidden OSPF interface on said active processor means and a hidden OSPF interface on said standby processor means;
- means for connecting said hidden OSPF interface of said active processor means

to said hidden OSPF interface of said standby processor means over a communications Link;

means for synchronizing an OSPF routing database using an OSPF protocol over said hidden OSPF interface, such that said OSPF routing database is synchronized when said hidden OSPF interface of said active processor means and said hidden OSPF interface of said standby processor means reach a full adjacency state;

means for transferring OSPF protocol information from said hidden OSPF interface of said active processor means to said hidden OSPF interface of said standby processor means over said communications link to mirror states of said active processor means and standby processor means;

means for removing said hidden interface of said active processor means and said hidden interface of said standby processor means; and

means for assuming control by said standby processor means when a failure is detected in said active processor means.

40. (Original) The system of claim 39 wherein said OSPF protocol information is OSPF configuration information, OSPF adjacencies information, OSPF interface information and OSPF global protocol information.

41. (Original) The system of claim 39 wherein said OSPF configuration information is determined from Command Line Interface (CLI) commands stored in a datastore.

42. (Original) The system of claim 39 further comprising:

means for updating network link protocol information at said active processor

means; and

means for forwarding said updated network link protocol information to said

standby processor means.

43. (Original) The system of claim 39 wherein said means for forwarding is a process based )n a Database Exchange Process of the OSPF protocol.

44. (Original) The system of claim 39 further comprising:

means for processing identical OSPF packets after synchronizing said link configuration and link protocol states between said active processor and said standby processor.